

## DEHUMIDIFIER WALL- & FLOORMODELS

Calorex® Dehumidifiers.

	Through wall model	Through wall model	Wall model	Wall model	Floor model	Floor model
Type.	34-183330	34-185560	34-183310	34-185540	34-187510	34-188110
Water cap. l/day at 60 %						
R.H. af 30°C room temperature.	30 l	60 l	30 l	60 l	75 l	110 l
Minimum operating temperature	0°C	0°C	0°C	0°C	0°C	0°C
kW	0,75	1,2	0,75	1,2	1,5	2,1
Volt	230	230	230	230	230	400/3N
IP	45	45	45	45	45	45
Noise level @ 3m. db/(A)	46	47	48	48	48	48
Airflow m <sup>3</sup> /hour	390	750	440	740	1180	1180
Condensate drainpipe. D=mm	10	10	10	10	22	22
Option for LPHW. (heater)	3 kW	5 kW	3 kW	5 kW	9 kW	9 kW
<b>Measurement</b>						
Width in mm	875	1300	780	1245	1520	1520
Depth in mm	290	290	255	255	380	380
Height in mm	745	745	653	653	791	791
Kg	45	70	40	60	150	152
Grating for in/outlet in mm	160 x 560	202 x 1170	-	-	-	-

Please contact our sales department for more information