

# CARTRIDGE FILTERS, SAND FILTERS, PREFILTERS & BALANCE TANKS

## CARTRIDGE FILTERS

### RTL CARTRIDGE FILTERS

RTL toploaded cartridge filter made in ABS plastic. The filter has a built-in by-pass.  
Max water temperature 45° C. Max water pressure 2,0 bar.

#### Size

Filter area m<sup>2</sup> / sq.ft

Max flow m<sup>3</sup>/ hour

Pipe connection

#### Measurement

Height mm

Diameter mm

#### Part number

#### RTL cartridge filter

01. Lockring for lid.

02. Air screw kit.

03. O-ring for air screw.

05. O-ring for filter.

06. Filter.

07. Screw for lock.

08. Lock.

11. Base for filter.

12. Complete lid with pos. 2-3-4-5.

Adaptor 2"x 50mm for glue.

	RTL50	RTL75
Filter area m <sup>2</sup> / sq.ft	4,6 / 50	6,9 / 75
Max flow m <sup>3</sup> / hour	12	18
Pipe connection	50 mm.	50 mm.
Height mm	500	670
Diameter mm	210	210

pare part number	
4,6m <sup>2</sup>	6,9m <sup>2</sup>
49-600001	49-600001
49-310002	49-310002
-	-
49-600005	49-600005
48-709046	48-709069
49-600007	49-600007
49-600008	49-600008
41-700010	41-700010
49-600012	49-600012
41-170234	41-170234

