



welldana®



| | Welldana Varenummer | 34-180628 | 34-180630 | 34-180632 | 34-180640 | 34-180642 |
|--------------------------------------|----------------------------|---|------------------|------------------|------------------|------------------|
| Info | Til pool (m ³) | 30-60 | 40-75 | 50-95 | 65-120 | 90-160 |
| | Type | Full Inverter | | | | |
| | Kølemiddel | R32 | | | | |
| | Volt / Hz | 230V~ / 50Hz | 230V~ / 50Hz | 400V/3N~ / 50Hz | 400V/3N~ / 50Hz | 400V/3N~ / 50Hz |
| | Funktion | Opvarmning og køling | | | | |
| | Godkendelse | CE | | | | |
| | Parameter | Ydelse ved luft 15⁰ og vand 26⁰. Luftfugtighed 70% | | | | |
| Kapacitet opvarmning (KW) | | 2.3~9.5 | 2.87~12.5 | 4.65~16.0 | 4.57~19.2 | 5.57~22.7 |
| Forbrug (kW) | | 0.32~2.03 | 0.41~2.55 | 0.63~2.92 | 0.80~3.98 | 0.80~5.04 |
| COP | | 7~4 | 7~4 | 7.38~5.48 | 6.96~4.82 | 6.96~4.50 |
| Nominal strøm (A) | | 15.0 | 15.0 | 10.0 | 15.0 | 15.0 |
| Max strøm (A) | | 20.0 | 20.0 | 20.0 | 20.0 | 20.0 |
| Laveste driftstemperatur | | -15 C | -15 C | -15 C | -15 C | -15 C |
| Blæser hastighed (RPM) | | 400-600 | 400-600 | 400-600 | 400-600 | 400-700 |
| Lydeniveau (Sound Pressure) 1m dB(A) | | 40-48 | 41-48 | 44-50 | 45-52 | 45-54 |
| Tilslutning (mm) | | 50 | | | | |
| Anbefalet driftsflow (m3/h) | | 6.5 | 7 | 8.9 | 9.1 | 9.7 |
| Max tryktab (max) MMS | | 5.5 | 6 | 6 | 11 | 11 |
| Visuelt | Kabinet | Pulverlakeret metalkabinet | | | | |
| | | Black | | | | |
| | Display | | | | | |
| | Display | Bluetooth display og vandtæt boks | | | | |
| | Montage | Kaster luften ud i toppen | | | | |
| | Smart Control | | | | | |
| | Wifi Modul & APP | | | | | |
| | Ja | | | | | |
| Tilbehør | Manual | DK/UK/SE | DK/UK/SE | DK/UK/SE | DK/UK/SE | DK/UK/SE |
| | Vibrationsdæmpende ben | Ja/gummi | Ja/gummi | Ja/gummi | Ja/gummi | Ja/gummi |
| | Tilslutning (mm) | Ø 50 mm | Ø 50 mm | Ø 50 mm | Ø 50 mm | Ø 50 mm |
| | Rubber Ring | Rubber | Rubber | Rubber | Rubber | Rubber |
| | Dræn tilslutning | Gummi | Gummi | Gummi | Gummi | Gummi |